

## Model 1300 Anhydrous Toolbar Specifications

Working Widths	15', 20', 27-1/2', 30', 32-1/2', 35', & 37-1/2'
Mainframe & Wing Tubing	7" x 5" Rectangular Tubing
Front Hitch	6" x 4" Rectangular Tubing A-Frame Style Hitch
Transport Width	17' 3" - 15' & 20' are rigid frame bars
Transport Height	27-1/2' & 30' - 11' 6" 32-1/2' & 35' - 12' 6" 37-1/2' - 13' 6"
Mainframe Wheels (single or tandem)	12.5L x 15 - 8ply
Wing Wheels	12.5L x 15 - 8ply (all hydraulically operated - no pin adjust)
Rear Hitch Assembly	Rigid or Floating with Telescoping Drawbar
Rephasing Lift System	Standard Equipment
Safety Lighting System	Standard Equipment
Combination Hitch Clevis (Single - Double)	Standard Equipment
Safety Chain	Standard Equipment
Saddle Clamp Wheel Legs	Standard Equipment
Rigid Shank Mounts w/20" Spring Loaded Coulter	Optional
Auto-Reset Shank Mounts w/20" Spring Loaded Coulter	Optional
18" Trash Titan Disk Sealer	Optional
Water Rinse Tank w/Toolbox	Optional
Monitor Mounting Bracket (Raven/Hinicker)	Optional
Row Markers	Available only on 30'
500 Gallon Mounted Liquid Tank	Optional

**Progressive Farm Products, Inc.**  
**19500 N 1425 East Road**  
**Hudson, IL 61748**  
**(309) 454-1564**

Specifications subject to change without notice or obligation.