

## Model 1500 Anhydrous Toolbar Specifications

|   |   |
|---|---|
| Working Widths                                      | 37-1/2', 40', 42-1/2', 45', 47-1/2' & 50'                   |
| Mainframe & Wing Tubing                             | 7" x 5" Rectangular Tubing                                  |
| Front Hitch   | 6" x 4" Rectangular Tubing A-Frame Style Hitch              |
| Transport Width (even rows)                         | 40' & 45' - 17' 3"      50' - 19' 3"                        |
| Transport Width (odd rows)                          | 37-1/2' & 42-1/2' - 17' 8"      47-1/2' - 19' 9"            |
| Transport Height                                    | 37-1/2' to 45' - 12'      47-1/2' & 50' - 13' 6"            |
| Mainframe Wheels (single or tandem)                 | 12.5L x 15 - 8ply   |
| Wing Wheels   | 12.5L x 15 - 8ply (all hydraulically operated-nopin adjust) |
| Rear Hitch Assembly                                 | Rigid or Floating with Telescoping Tongue                   |
| Rephasing Lift System                               | Standard Equipment  |
| Safety Lighting System                              | Standard Equipment  |
| Combination Hitch Clevis (Single - Double)          | Standard Equipment  |
| Safety Chain  | Standard Equipment  |
| Saddle Clamp Wheel Legs                             | Standard Equipment  |
| Rigid Shank Mounts w/20" Spring Loaded Coulter      | Optional  |
| Auto-Reset Shank Mounts w/20" Spring Loaded Coulter | Optional  |
| 18" Trash Titan Disk Sealer                         | Optional  |
| Water Rinse Tank w/Toolbox                          | Optional  |
| Monitor Mounting Bracket (Raven or Hinicker)        | Optional  |
| Row Markers   | Not Available   |
| 500 Gallon Mounted Liquid Tank                      | Optional  |

**Progressive Farm Products, Inc.**  
**19500 N 1425 East Road**  
**Hudson, IL 61748**  
**(309) 454-1564**

Specifications subject to change without notice or obligation.