

## MODEL 2400 SIDEDRESS APPLICATOR SPECIFICATIONS

Available sizes (working width)	15' rigid, 22 1/2', 27 1/2', 32 1/2'
Mainframe & Wing Tubing	7" x 7" x 3/8" square tubing
Front Hitch	7" x 7" x 3/8" square tubing
Transport Width	16 1/2'
Transport Height	22 1/2' - 9' 6", 27 1/2' - 12'6", 32 1/2' - 14'8"
16.5 x 16.1 10 ply Mainframe Tires/Wheels	Optional
18.4 x 26 - 10 ply Mainframe Tires/Wheels	Optional
13.6 x 38 - 12 ply Mainframe Tires/Wheels	Optional
14.9R x 46 8 star radial - 14 ply Tires/Wheels	Available on 1600 Gallon model only
750 Gallon Tank	Optional
1000 Gallon Tank	Optional
1600 Gallon Tank	Optional
Coulter Assembly - 1200# Trip Pressure	20" swivel with 32" crop clearance
Patented Midmount Design	Standard Equipment
Safety Lighting System	Standard Equipment
Combo Hitch Clevis (single/double)	Standard Equipment
Adjustable Axle	Standard Equipment
No Drip Manifold System	Standard Equipment
2" Rear Quick Fill	Standard Equipment
Ground Drive Pump System	John Blue Single or Double Piston Pump
Hydraulic Pump w/Teejet Metering System	Optional - in lieu of ground drive pump system
Knife Kit	Optional
Liquid Injection Kit	Optional
Water Rinse Tank w/toolbox	Optional

**Progressive Farm Products, Inc.**  
**19500 N. 1425 East Road**  
**Hudson, IL 61748**  
**(309) 454-1564**

Specifications subject to change without notice or obligation.