

**MODEL 2500 - FRONT FOLD - 1600 GALLON SIDEDRESS
APPLICATOR SPECIFICATIONS**

| | |
|-------------------------------------|---|
| Available sizes (working width) | 60' |
| Mainframe & Wing Tubing | 7" x 7" x 3/8" square tubing |
| Front Hitch | Extendable |
| Transport Width | 11' 10" |
| Transport Height | 8' 6" |
| Transport Length | 37' 6" |
| Field Length | 31' 0" |
| 14.9R x 46 - 8 Star Radial (14 ply) | standard equipment |
| Mainframe Wheels | |
| Standard Tank Capacity | 1600 gallon |
| Injection Coulter Assy. | 20" swivel coulter with knife or nozzle injection |
| Patented Midmount Design | standard equipment |
| Safety Lighting System | standard equipment |
| Combo Hitch Clevis(single/double) | standard equipment |
| Adjustable Axle | standard equipment |
| No Drip Manifold System | standard equipment |
| 2" Rear Quick Fill | standard equipment |
| Hydraulic Pump w/TeeJet Monitor | Optional |
| Knife Kit | Optional |
| Liquid Injection Kit | Optional |
| Water Rinse Tank w/toolbox | Optional |

**Progressive Farm Products, Inc.
19500 N. 1425 East Road
Hudson, IL 61748
(309) 454-1564**

Specifications subject to change without notice or obligation.